

Universal GSM Alarm Communicator for Primary or Redundant Signaling

Uplink 2500

Compact and easy-to-install, the Uplink 2500 uses the industry standard GSM (Global System for Mobile Communications) network protocol for instant transmission of alarm signals to a Central Monitoring Station. Simply connect the compact 2500 to the siren output and up to three other outputs for universal compatibility with virtually any alarm panel as a primary communicator or wireless backup to a phone line.

Uplink 2500 Key Features



- Primary or redundant GSM communications
- Perfect for residential or commercial alarm systems
- Universal summary data communicator
- Power from the alarm panel or 12V DC supply to detect burglary or fire condition



- Smart siren/bell sampling
- 4 inputs, 2 outputs
- Contact ID, SIA, 4/2 (20 PPS) and Modem II/IIIa2



- Installs in minutes
- Email notification for instant alerts
- Website control & status 24/7



- Cost-effective device and network service
- Flat-rate billing for improved dealer profitability
- Works with any central station - no programmer required

Uplink's dealer support:

- Instant activation by secure dealer website or live operator
- Email Notifications for instant alerts, Website Control & Status 24/7
- Expert Support from a live technical specialist 8am-8pm Monday through Friday
- Dealer website for activation/deactivation, trouble-shooting, remote programming and on-demand status and signal strength testing, analysis tools and more



* 12V DC Required

Uplink 2500

Universal Summary Data Communicator

1.888.9.UPLINK | 1.888.987.5465

www.uplink.com
sales@uplink.com

A Trusted Partner

Uplink 2500

The Uplink 2500 is a member of the Uplink family of wireless alarm communicators. Our products deliver the unique combination of reliable technology and superior value that has made Uplink the security industry's most trusted source for alarm communicators since 1996. GSM or CDMA protocols, primary or back-up applications, summary or full data reporting, there is an Uplink wireless alarm communicator for virtually any security system on the market today. With hundreds of thousands of installed communicators throughout the United States and Canada, Uplink delivers on its promise as the security dealer's trusted partner.

Plus, Uplink wireless communicators are backed by the unique combination of the proprietary ISO-27001 certified network service offering and a robust dealer web management tool.

For more information, visit the Uplink website and sign up to become an Uplink dealer at www.uplink.com.



Uplink 2500 Product Specifications

INPUTS	
Siren/Bell Sampling	<ul style="list-style-type: none">• Input 1: Connect to Siren/Bell (distinguishes between Burg/steady and Fire/pulsed) or programmable to 12 volts
Other	<ul style="list-style-type: none">• Connect up to three 12V inputs
OUTPUTS & REPORTING	
Central Station	<ul style="list-style-type: none">• Contact ID, SIA, 4/2 (:20 PPS), Modem II/IIIa2, Internet
Automated Reports	<ul style="list-style-type: none">• Weekly or daily test, low voltage
Relays	<ul style="list-style-type: none">• Two configurable relay outputs to send signal to alarm panels or control other devices
Emails	<ul style="list-style-type: none">• Send email alerts to end users or alarm company
POWER REQUIREMENTS	
	<ul style="list-style-type: none">• 12V DC from alarm panel or external power supply• 2A max on transmit (400 ms)• 28MA standby
RADIO	
Type	<ul style="list-style-type: none">• Dual band
GSM	<ul style="list-style-type: none">• Maximum allowable
Transmit Power	<ul style="list-style-type: none">-1.0W at 1800/1900 MHz-2.0W at 850/900 MHz
DIMENSIONS	
Height	<ul style="list-style-type: none">• 4.75 inches
Width	<ul style="list-style-type: none">• 3.3 inches
Depth	<ul style="list-style-type: none">• 1.3 inches
DEALER WEBSITE	
	<ul style="list-style-type: none">• Activate & Deactivate units• Adjust settings and reporting• Request status and signal strength• View signal history• Control inputs and outputs and notifications
OPTIONAL ACCESSORIES	
	<ul style="list-style-type: none">• Magnet mount antenna with 9 ft cable• 8 inches tall high gain antenna with articulating joint



1.888.9.UPLINK | 1.888.987.5465

www.uplink.com
sales@uplink.com

©2011 Uplink Security LLC. All rights reserved. Uplink is a trademark of Uplink Security LLC.